



MODEL		MTX9HP24	
Cooling	Nominal capacity (min-max)	Btu/h	9000 (3100 - 11600)
	Nominal capacity (min-max)	W	2640 (909 - 3400)
	Absorbed electrical power (min-max)	W	732 (100 - 1240)
	EER		3,60
	Pdesignc	kW	2,80
	SEER	W/W	6,30
	Energy efficiency class		A++
Heating	Nominal capacity (min-max)	Btu/h	10000 (2800 - 11500)
	Nominal capacity (min-max)	W	2930 (820 - 3370)
	Absorbed electrical power (min-max)	W	733 (120 - 1200)
	COP		4,00
	Pdesignh (Average )	kW	2,60
	SCOP (Average )	W/W	4,00
	Energy efficiency class (Average)		A+
	Pdesignh (Warmer )	kW	2,60
	SCOP (Warmer )	W/W	5,10
Energy Efficiency Class (Warmer)		A+++	
INDOOR UNIT		MTXI9HP24	
Power Supply	V-Ph-Hz	220-240, 1, 50	
Air flow (Hi / Mi / Lo)	m3/h	466/360/325	
Sound pressure level (Hi / Mi / Lo / Si)	dB(A)	38,5/32/25/21	
Sound power level (Hi)	dB(A)	54,0	
Dimensions (LxWxH)	mm	805x194x285	
Dimensions with packaging (LxWxH)	mm	870x270x365	
Net / Gross Weight	kg	7,6/9,7	
OUTDOOR UNIT		MTXO9HP24	
Power Supply	V-Ph-Hz	220-240, 1, 50	
Max. power consumption	W	2150	
Air flow	m3/h	1750	
Sound pressure level	dB(A)	55,5	
Sound power level	dB(A)	62,0	
Dimensions (LxWxH)	mm	720x270x495	
Dimensions with packaging (LxWxH)	mm	835x300x540	
Net / Gross Weight	kg	23,2/25,0	
REFRIGERANT DATA			
Refrigerant	Type		R32
	GWP		675
	Refrigerant charge	kg	0,55
Refrigerant Pipe	Liquid / Gas	mm(inch)	Φ6,35(1/4") / Φ9,52(3/8")
	Max refrigeration line length	m	25,0
	Max altitude difference	m	10,0
	Refrigerant pre-charge	m	5,0
	Additional FGAS	g/m	12,0
Operating temperature	Internal (cooling / heating)	°C	17~32/0~30
	External (cooling / heating)	°C	-15~50/-15~30

A++



Inverter



Wi-Fi  
Optional



Refrigerant  
Gas



CE Marking



Regulation  
2002/95/EC